


COURSALIS & COURSALIS E

High-performance air curtains with heating
mode and remote control

TERTIARY



HIGH PERFORMANCE AIR CURTAIN
FOR TERTIARY. REACH UP TO 3m

COURSALIS & COURSALIS E

FUNCTION

COURSALIS air curtains create an invisible air barrier for businesses adaptable to any size entrance.

They are an ideal solution to maintain **interior comfort** (heating in winter and air conditioning in summer), maintaining a **clean atmosphere** of odors and insects, as well as dust and pollution coming from outside the premises.

ADVANTAGES

- You will **reduce drafts** coming from outside and maintain the temperature inside your business without having to close the door.
- In addition, with the **remote control** you can start it, stop it or change the air flow speed as well as the type of air temperature (natural or heat) as needed from anywhere nearby.

CHARACTERISTICS

- Exclusive arch design, light and superfine.
- High performance and low sound level.
- Metallic housing with white colour finishing coat.
- Motor 380V 50Hz (COURSALIS and COURSALIS E).
- Motor 110V y 230V 60Hz (COURSALIS).
- Sizes: width 1000, 1500 and 2000mm.
- COURSALIS**: only low or high speed air.
- COURSALIS E**: with heating, equipped with electrical coil.
- Includes external remote control.
- Designed for horizontal mural installation.
- Easy adjustable air direction.
- With operating indicator LED (ambient or heating, air speed and start-stop).
- Mounting brackets on wall.
- Reach up to 3m.
- Presence switch available to stop/start the air curtain with the passage of people through the entrance.



APPLICATIONS

- Schools
- Malls
- Stores
- Supermarkets
- Train stations
- Hotels
- Restaurants
- Pubs
- Offices
- Banks
- Gas stations
- Logistics centers
- Industries, food industries
- Hospitals, clinics, health centers
- Veterinary clinics
- Refrigerated warehouses



50Hz

COURSALIS


Size	1000	1500	2000
Air flow (m³/h)	1600	2500	3380
Tension (V-Hz-Fase)	220V - 50Hz - Single phase		
Velocidades	2		
Height application (m)	3		
Fan consumption (W)	165	230	330
Fan intensity (A)	0,75	1,045	1,5
Control	Remote and manual		
Sound level (Lp dB(A)6m)*	42	43	44
Height (mm)	220	220	220
Wide (mm)	1150	1650	2150
Depth (mm)	195	195	195
Net weight (Kg)	15,6	21,8	26,7

COURSALIS E

Size	1000 E	1500 E	2000 E
Air flow (m³/h)	1100	1800	2400
Heating power (kW)	4,4	5,5	10
Tension (V-Hz-Fase)	380V - 50Hz - Three phase		
Speed	2		
Height application (m)	3		
Fan consumption (W)	180	220	320
Fan intensity (A) + coil	11,64	14,47	26,32
Control	Remote and manual		
Sound level (Lp dB(A)6m)*	42	43	44
Height (mm)	220	220	220
Wide (mm)	1150	1650	2150
Depth (mm)	195	195	195
Net weight (Kg)	17,6	24,7	29,6

* Total sound pressure level at the point of maximum flow measured in dB(A) in the suction measured in free field at a distance of 6m from the source.

● Reaching (m)




60Hz

COURSALIS


Size	900	1200	1500
Air flow (m³/h)	1600	1700	2100
Tension (V-Hz-Fase)	110/220V - 60Hz - Single phase		
Velocidades	2		
Height application (m)	3		
Fan consumption (W)	150	200	230
Control	Remote and manual		
Sound level (Lp dB(A)6m)*	45	46	47
Height (mm)	220	220	220
Wide (mm)	1050	1350	1650
Depth (mm)	195	195	195
Net weight (Kg)	14,9	18	21,3

* Total sound pressure level at the point of maximum flow measured in dB(A) in the suction measured in free field at a distance of 6m from the source.

● Reaching (m)



DIMENSIONS



	A	F	G
900	1050	195	220
1000	1150	195	220
1200	1350	195	220
1500	1650	195	220
2000	2150	195	220



VORTICE GROUP COMPANIES

VORTICE S.P.A

Strada Cerca, 2
Frazione di Zoate
20067 Tribiano
(Milan) Italy
Tel. (+39) 02 906991
Fax (+39) 02 90699625
vortice.com

VORTICE LIMITED

Beeches House-Eastern
Avenue Burton upon Trent
DE13 0BB United Kingdom
Tel. (+44) 1283 492949
Fax (+44) 1283 544121
vortice.ltd.uk

VORTICE INDUSTRIAL S.R.L.

Via B. Brugnoli 3,
37063 Isola della Scala
(Verona) Italy
Tel. (+39) 045 6631042
Fax (+39) 045 6631039
vorticeindustrial.com

CASALS VENTILACIÓN AIR INDUSTRIAL S.L.

Ctra. Camprodon, s/n 17860
Sant Joan de les
Abadesses
(Girona) Spain
Tel. (+34) 972720150
casals.com

VORTICE LATAM S.A.

Bodega #6
Zona Franca Este Alajuela,
Alajuela 20101
Costa Rica
Tel. (+506) 2201 6934
vortice-latam.com

VORTICE VENTILATION SYSTEM

(Changzhou) Co.LTD
No. 388 West Huanghe Road
Building 19, Changzhou
Post Code: 213000 China
Tel. (+86) 0519 88990150
Fax (+86) 0519 88990151
vortice-china.com

The descriptions and illustrations in this catalogue are intended to be indicative and not binding. Without prejudice to the essential characteristics of the products described and illustrated here, CASALS VENTILACIÓN reserves the right to make, at any time and without notice, changes to parts, aesthetic details or supply of accessories to its products that are deemed to be appropriate for improvement or for any construction or commercial requirement.

This printout completely cancels and replaces all the previous ones.