



50/60 Hz R O O F

RESIDENTIAL/TERTIARY/INDUSTRIAL > R O O F

[www.casals.com](http://www.casals.com)



# > R O O F F A N S <



The range of Casals roof fans covers multiple applications: residential, commercial or tertiary and industrial.

Available in 50Hz and 60Hz, ATEX version, fire applications, constructions in aluminum or polyamide, centrifugal and axial impellers.



KIT TE	KIT TM	
		Roof kit for case fans (KIT TE)
		Metallic roof kit for case fans (KIT TM)



CTH3	CTH3 - A	CTH4
Roof fan, ABS cowl 400°C/2h	Roof fan, AL cowl 400°C/2h	Roof fan, vertical discharge



Q máx. 50Hz	27.090 m <sup>3</sup> /h	39.590 m <sup>3</sup> /h	27.090 m <sup>3</sup> /h
Q máx. 60Hz	19,130 CFM	40,580 CFM	19,130 CFM

BT ROOF 2 SBP	BT ROOF 2 SB
Centrifugal roof fan with backward impeller. Horizontal discharge	
BT ROOF 2 SB : Without flanges on the base	
BT ROOF 2 SBP : With flanges on the base	

Q máx. 50Hz	1.880 m <sup>3</sup> /h	110V / 230V
Q máx. 60Hz	1,330 CFM	

FOCCETA	
	Centrifugal roof fan for fireplaces and barbecues

Q máx. 50Hz	750 m <sup>3</sup> /h
Q máx. 60Hz	535 CFM

